

Titan.




JOHN BERGER



SCAN WITH YOUR MOBILE
TO FIND US ONLINE

Titan.

MICRO TRACK SYSTEM



Micro Track System

234-84253

Application

1. Design for boutique, galleries, or other display applications
2. Light up the products by accent lighting

User Friendly

1. Lighting can be molded easily without using heavy tools, handling flexible and intuitively
2. The power and mechanical combination, thus decreasing man power
3. Especially flexible during seasonal changes or simple remodeling

Safety

Stainable and stable structure

- Materials
1. LED fixture/ aluminum and easily recycle
 2. Micro tracks/ extruded aluminum and anodized finishing
 3. Accessories/ sheet metal
 4. Shelf/ reinforced glass

red dot design award
winner 2012



Titan. Your Brightest Choice



Titan.



■ U-Shape Micro Track
Cabinet Track System



01-04



■ H-Shape Micro Track System
Wall Shelf Display System



05-10



■ L-Shape Micro Track
Free-standing Display System



11-16



■ Micro Cabinet Spotlight



17-20

*The anodizing black color of Micro Track System is not designed for long-term UV exposure.
Please check with your sales contact window for special treatment on Micro Track System.

Titan.

Mini Track Kit

- Very easy install, and Plug in-and-out the light head.
- By clever on-off switch, end user can easy change the position of the light head.
- Different set of light heads available on request.
- 3 beam angles of Optical lens provide precise and uniform light effect.
- Two drivers 12W, 8W available for the kit set.



Component List

Type	Item Code	QTY
Track	1. TU-0.45M	3
	2. TU-ECAP	1
Luminaire	3. [1] Micro Track Light(1.5W) TU12-345-501/8 [2] Micro Track Light(1.5W) TU12-345-501/7 [3] Micro Track Light(1.5W) TU12-345-501/6	8
Other	4. TU-T12(AC100-240V, Max 12W)	1
	5. TU-J05(DC12V , Max 6A)	2



0.45Mx3



0.45Mx2


■ TU12-345-501/8




■ TU08-245-501/5



■ U-Shape Micro Track Cabinet Track System



1. Connect AC(100-240V) cable to the transformer.
2. Fix the cable with gasket and screw.
3. Insert TU-T08 or TU-T12 into U-shape micro track.
4. Screw TU-T08 or TU-T12 into position.



U-Shape

TU-0.3M/0.45M/0.6M/0.9M/1M U-shape micro track: Aluminium, anodized Surface mounted DC 12V, MAX 6A L = 300mm; 500mm 600mm; 900mm Color: ■ BK	
---	--

For U-Shape

TU-J01 Straight-connector Plastic DC 12V, MAX 6A Color: ■ BK	
--	--

TU-J02 L-connector Plastic DC 12V, MAX 6A Color: ■ BK	
---	--

TU-J05 Adjustable-connector plastic DC 12V, MAX 6A Color: ■ BK	
--	--

TU-L01 Live end Plastic DC 12V, MAX 6A Color: ■ BK	
--	--


TU-ECAP End cap Plastic Color: ■ BK	
--	--

TU-F01 Aluminium, anodized Color: ■ BK	
--	--

TU-L01 Intermediate power connector Plastic Coupler for all-type micro track DC 12V, MAX 6A Color: ■ BK	
--	--


TU-F01 Aluminium, anodized Color: ■ BK	
--	--

Installation manual




Micro Spotlight

SA-501A Input: AC 100-240V Po: MAX 8W Vo: DC 12V, MAX 1A Color: ■ BK	
SA-501B Input: AC 100-240V Po: MAX 8W Vo: DC 12V, MAX 1A Color: ■ BK	
SA-501C Input: AC 100-240V Po: MAX 8W Vo: DC 12V, MAX 1A Color: ■ BK	
SA-501D Input: AC 100-240V Po: MAX 8W Vo: DC 12V, MAX 1A Color: ■ BK	






Installation



Component List of Horizontal Bracket Version

Type	Item Code	QTY
Track	1. TH-1.5M	2
	2. AJ-01	2
	3. AJ-02	4
	4. AJ-011	1
	5. AJ-021	2
	6. TC-L01	1
	7. TH-EGAP	4
Luminaire	8. Micro Track Light(1.5W)	6
Other	9. LLV20W12 UNI(AC100-240V)	1



JOHN BERGER





H-Shape Micro Track System

Combination of Wall Shelf Display System

Micro Spotlight

Light head: aluminium, anodized
Stick: copper, powder-coated.
Adapter: plastic
Input: DC 12V
LED: OSRAM
LED color: □ CW NW ■ WW
Color: ■ BK

1.5W(350mA) or 3.4W(700mA)



*For reference of dimension only, board AJ-011 and AJ-021 not for sell.

H-Shape

H-Shape

Combination of Wall Shelf Display System

TH-0.3M/0.45M/0.6M/0.9M/1M/1.5M

TITAN H-shape micro track:
Aluminium, anodized
Surface mounted
DC 12V, MAX 6A
L=300mm;450mm
600mm;900mm
1000mm;1500mm
Color: ■ BK

TH-J01

Straight-connector
Plastic
DC 12V, MAX 6A
Color: ■ BK

TH-L01

Live end
Plastic
DC 12V, MAX 6A
Color: ■ BK

TH-ECAP

End cap
plastic
Color: ■ BK

AJ-01

Bracket
Steel, powder-coated
For H & L-shape micro track
Color: ■ BK

AJ-02

Bracket
Steel, powder-coated
For H & L-shape micro track
Color: ■ BK

TC-L01

Intermediate power connector
Plastic
Coupler for all-type micro track
DC 12V, MAX 6A
Color: ■ BK

Horizontal Bracket

Horizontal Board

AJ-011

L:1000mm
W:300mm
H:9mm

AJ-021

L:1000mm
W:300mm
H:16mm

Tilted Board

AJ-022

L:1000mm
W:300mm
H:45mm

TC-L01x2

Drivers & Accessories

Constant Voltage Driver

Terminal block (screw)  Quick connector  Push quick connector 

Available for 1.5W (350mA) LED



Driving Fixture QTY



4  8

6  12

20  37

Available for 3.4W(700mA) LED



Driving Fixture QTY



3  5

LLV12W12 UNI 

Input: AC100-240V
Po: MAX 12W
Vo: DC 12V, MAX 1000mA
L:85 W:40 H:22

LLV20W12 UNI 

Input: AC100-240V
Po: MAX 20W
Vo: DC 12V, MAX 1670mA
L:167 W:38.4 H:30


LLV60W12 

Input: AC220-240V
Po: MAX 60W
Vo: DC 12V, MAX 5000mA
L:190.5 W:88 H:35.5

LHV60W12 

Input: AC220-240V
Po: MAX 60W
Vo: DC 12V, MAX 5000mA
L:190.5 W:88 H:35.5





Component List

Type	Item Code	QTY
Track	1.TL-1.8M	4
	2.AJ-05(L)	6
	3.AJ-05(R)	6
	4.TH-ECAP	4
Luminaire	5.Micro Track Light(1.5W)	12
	6.AJ-05A	1
	7.AJ-05B (with LLV20W12 UNI)	1
	8.AJ-05C	3
Other		



reddot design award
winner 2012





JOHN BERGER



L-Shape

L-Shape Micro Track
Combination of Free-standing Display System

L-Shape

TL-0.6M/0.9M/1M/1.2M/1.5M/1.8M
L-shape micro track:
Aluminium, anodized
Combination or Surface mounted
DC 12V, MAX 6A
L=600mm; 900mm; 1000mm;
1200mm; 1500mm; 1800mm
Color: ■ BK




For L-Shape


AJ-05(L & R)
Steel, powder-coated,
with screw kit& PC gasket.
Color: ■ BK




TC-L01
Intermediate power connector
Plastic
Coupler for all-type micro track
DC 12V, MAX 6A
Color: ■ BK



TH-ECAP
End cap
plastic
Color: ■ BK



AJ-05A
Steel, powder-coated.
Color: ■ BK




AJ-04B / AJ-05B / AJ-06B
Steel, powder-coated, with plug.
Color: ■ BK

Included:

TH-ECAP x 4
TC-L01 x 4
AJ-05D x 4
Screw x 8
Transformer x 1

Base type Transformer type Input Output
AJ-04B L/N/V/2W/2L/UNI AC 110-240V DC 12V 24W
AJ-05B L/L/V/2W/2L/UNI AC 110-240V DC 12V 24W
AJ-06B L/H/V/6W/12 UNI AC 220-240V DC 12V 60W






Drivers & Accessories

Installation

Constant Voltage Driver & optional component

Terminal block (screw) Quick connector




Step 1

Step 2

Driving Fixture QTY

1.5W Micro Spotlight	2W Micro Bar 300mm	3.4W Micro Spotlight
8	0	0
5	2	0
3	0	2
⋮	⋮	⋮
A	B	C
1.5W x A	2W x B	3.4W x C
$12W \geq$		



Step 3

1.5W Micro Spotlight	2W Micro Bar 300mm	3.4W Micro Spotlight
13	0	0
8	4	0
5	6	0
0	3	4
0	1	5
⋮	⋮	⋮
A	B	C
1.5W x A	2W x B	3.4W x C
$20W \geq$		

Step 4

$60W \geq$ **1.5W x A** + **2W x B** + **3.4W x C**

Push quick connector



Micro Cabinet Spotlight






Light head: aluminium, anodized
Stick: copper, powder-coated.



LED: OSRAM 1.2W or 3W

LED color: □ CW ■ NW ■ WW

Color: ■ BK



Light head: aluminium, anodized
Stick: copper, powder-coated.
LED: OSRAM 1.2Wx2 or 3Wx2
LED color: □ CW ■ NW ■ WW
Color: ■ BK



Constant Current Driver

 Terminal block (screw)  Quick connector



Available for (350mA) LED

Driving Fixture QTY
LSVC3AI-Z UNI  1.2Wx2 1.2Wx1

LFVCAI-Z UNI  1  or 1-3
Input:100-240V
output: 1-10.3V 350mA
L:55 W:40 H:20

LMC10W700-Z  1-2  or 2-4
Input:100-240V
output: 3.14V 350mA
L:73 W:40 H:16

LMC15W350-Z  4  or 7-9
Input:220-240V
output: 17.29V 350mA
L:85 W: 40. 4 H:22

LBG20W700-Z  5-6  or 10-13
Input:220-240V
output: 26.43V 350mA
L:85 W: 40. 4 H:22

LBG20W350-Z  7-8  or 13-17
Input:120-277V
output: 3.6-55.7V 350mA
L:116.4 W: 44 H: 30

Available for (700mA) LED

Driving Fixture QTY
LSVC3BI-Z UNI  3Wx1 3Wx2

LSC6W700-Z  1  or 1
Input:100-240V
output: 2-5V 700mA
L:55 W:39 H:20

LMC10W700-Z  1  or 2
Input:100-240V
output: 3.9V 700mA
L: 66.3 W: 38. 5 H: 22

LMC15W700-Z  2  or 3-4
Input:220-240V
output: 8.5-14V 700mA
L: 85 W: 40. 4 H: 22

LBC20W700-Z  3  or 5-6
Input:120-277V
output: 13-21V 700mA
L: 85 W: 40. 4 H: 22

LBC20W350-Z  7-8  or 7-8
Input:120-277V
output: 18-28V 700mA
L: 116.4 W: 44 H: 30

Accessories

Available for constant current 350mA

LDL-AC2-6 
Multi-lamp extension
cord 1007#22awg
L:1000/1500/2000/3000

LDL-AC2-3 
Multi-lamp extension
cord 1007#22awg
L:1000/1500/2000/3000

LDL-AC2 
Multi-lamp extension
cord 1007#22awg
L:1000/1500/2000/3000

Accessories

Available for constant current 700mA

LDL-AC2B 
Multi-lamp extension
cord 1007#22awg
L:1000/1500/2000/3000

LDL-AC2-3B 
Multi-lamp extension
cord 1007#22awg
L:1000/1500/2000/3000

LDL-AC2-6B 
Multi-lamp extension
cord 1007#22awg
L:1000/1500/2000/3000